ViviStrata Layers glass is low maintenance and may be used in a variety of applications to increase the daylight factor, as well as provide glare control within a building. Daylighting properties may aid in harvesting site energy throughout the space and reduce the requirement for electric lighting.

Recycled Content & Certifications

Configurations	Post- Industrial Recycled Content	Post- Consumer Recycled Content	Total Recycled Content	3 rd Party Certifications
ViviStrata Layers glass	0%	0%	0%	-

Green Building Standards

LEED[®] v3

EAp2/EAc1: Energy Performance – the use of glass may aid in harvesting site energy by increasing daylighting properties throughout the space and reducing the requirement for electric lighting. Please contact us for more information.

MR2: Construction Waste Management - packaging is designed to be reusable or recyclable. See below for details.

MR5: Regional Materials – this product is manufactured in Phoenix, AZ. Contact for extraction information.

IEQ8: Daylight & Views – Decorative glass may be used in a variety of applications to increase the daylight factor, as well as provide glare control within a building. Please contact us for more information.

LEED v4

EAp2/EAc2: Energy Performance - the use of glass may aid in harvesting site energy by increasing daylighting properties throughout the space and reducing the requirement for electric lighting. Please contact us for more information.

MRp2/MR5: Construction Waste Management - packaging is designed to be reusable or recyclable. See below for details.

MR3: Sourcing of Raw Materials (regional materials) - this product is manufactured in Phoenix, AZ. Contact for extraction information.

MR4: Material Ingredients – this product has a Health Product Declaration. Contact for details.

EQ2: Low-emitting Materials – inherently non-emitting sources. Contact for details.

EQ7: Daylight - Decorative glass may be used in a variety of applications to increase the daylight factor, as well as provide glare control within a building. Please contact us for more information.

Green Globes™

3.3.1: Energy Performance - the use of glass may aid in harvesting site energy by increasing daylighting properties throughout the space and reducing the requirement for electric lighting. Please contact us for more information.

3.5.4.1 Construction Waste – packaging is designed to be reusable or recyclable. See below for details.

3.7.2.1 Volatile Organic Compounds - inherently non-emitting sources. Contact for details.

3.7.3.1 Daylighting - Decorative glass may be used in a variety of applications to increase the daylight factor, as well as provide glare control within a building. Please contact us for more information.

Estidama Pearl Rating System: Design & Construction, Version 1.0

LBi-2.5: Material Emissions: Formaldehyde Reduction – inherently non-emitting sources. Contact for details.

LBi-7: Daylight & Glare – Decorative glass may be used in a variety of applications to increase the daylight factor, as well as provide glare control within a building. Please contact us for more information.

RE-R1/RE-1: Energy Performance: the use of glass may aid in harvesting site energy by increasing daylighting properties throughout the space and reducing the requirement for electric lighting. Please contact us for more information.

SM-R2/SM-13: Construction Waste Management - packaging is designed to be reusable or recyclable. See below for details.

SITES v2 Rating System

Materials C5.6: Use regional materials - this product is manufactured in Phoenix, AZ. Contact for extraction information.

Materials C5.8: Support transparency and safer chemistry - this product has a Health Product Declaration. Contact for details.

Construction C7.5: Divert construction and demolition materials from disposal - packaging is designed to be reusable or recyclable. See below for details.

Product Materials

Material	Description	Mainte- nance (0-5)*	Inherent Value (0-5)**	Biodegrad- able	Corrosion/ Wear Resistant	Rapidly Renewable	Recyclable	Scratch Resistant
Glass – Safety Laminated Decorative	Polyvinyl butyral (PVB) based thermoplastic interlayer laminated between two lites of glass.	4	0		x			
	signed as follows: 0 – High level of maintenance required to keep up product poppearance and performance characteristics	erformance a	nd aesthetics; 5	– Absolu	itely no mai	ntenanc	e requ	uired
**Inherent value ratings are a accompanied by robust scra	assigned based on the material's scrap value: 0 – No scrap value, or negative : p market	scrap value, a	ind/or no scrap	market; 5	i – High scra	ap value	,	

Processes

Process	Description
Glass etching	Physical etching process in which an artwork mask is applied to a glass surface that is then bead-blasted. Unmasked areas become more matte, whereas masked areas retain their original look. Beads are recycled within the process until the particles become too small to use.
Safety Laminated Decorative Glass Making	Polyvinyl butyral (PVB) based thermoplastic interlayer laminated between two lites of glass under heat and pressure to create a safety laminated glass.

Packaging Materials

Material	Туре	Description	Disposal
Cardboard	Spacers	Used to provide impact cushioning between a product and its package or between two products.	Reuse/Recycle
Paper	Sheets	Used to protect the finish on products.	Reuse/Recycle
Wood	Crate	Wood crates are made to fit onsite. Wood scraps are recycled into mulch. Crates are reused when possible.	Reuse/Recycle

Transport

Method	Туре	Description
Boat	Overseas	Some product components are shipped by cargo ship from overseas
Ground	Truck/Rail	Some incoming shipments and almost all outgoing shipments to customers are sent via ground transportation. This can include truck and often rail transport depending on the final destination. We are an EPA SmartWay® Transport Partner.

Maintenance & Use

Maintenance or Use	Description	Chemicals Required
Clean with Water and Mild Cleaner	This product requires a damp cloth and a mild, nontoxic cleaner for maintenance.	Mild, water-based cleaner
Daylight Factor	Decorative glass may be used in a variety of applications to increase the daylight factor, as well as provide glare control within a building.	NA
Energy Reduction	Glass may aid in harvesting site energy by increasing daylighting properties and reducing the requirement for electric lighting.	NA

Disposal

Method	Description
Not Recyclable	Product is not recyclable

Forms+Surfaces is dedicated to environmental responsibility. We maintain an Environmental Management System and are continually working to improve our impact through efficiency, material selection, vendor education, employee involvement, and an unwavering commitment to being exemplary corporate citizens. If you would like additional information, please contact our Sustainability Team at green@forms-surfaces.com

T 800.451.0410 | www.forms-surfaces.com

FORMS+SURFACES®

© 2015 Forms+Surfaces® | All dimensions are nominal. Specifications and pricing subject to change without notice. For the most current version of this document, please refer to our website at www.forms-surfaces.com.