Helio Bollards are designed to provide downward-facing light to help minimize light pollution and glare. They are low maintenance and easy to disassemble. Stainless steel and acrylic components are 100% recyclable. Stainless steel components have a high recycled content. The powdercoat finish is a low- or no-VOC finish, depending on color. Energy efficient lamp options are available.

Recycled Content & Certifications

Configurations	Pre-Consumer Recycled Content	Post-Consumer Recycled Content	Total Recycled Content	3 rd Party Certifications
Helio M30/K4 Security Bollard, Series 900, illuminated	contact	contact	contact	International DarkSky Approved*
Helio M30/K4 Security Bollard, Series 900, non-illuminated	contact	contact	contact	-
Helio Bollard, Series 900, illuminated (non-security)	contact	contact	contact	International DarkSky Approved*
Helio Bollard, Series 900, non-illuminated (non-security)	contact	contact	contact	-



^{*} Helio Bollard, Series 900 3000K is International DarkSky Approved

Green Building Standards

LEED® v3

SS8: Light Pollution - full light output data is available on Product Data Sheets. Contact for details.

MR2: Construction Waste Management - packaging is designed to be reusable or recyclable. See below for details.

MR4: Recycled Content - this product contains recycled material. Recycled content is shown above for all standard options.

MR5: Regional Materials - this product is manufactured in Pittsburgh, PA. Contact for extraction information.

LEED v4

SS6: Light Pollution Reduction - full light output data is available on Product Data Sheets. Contact for details.

MRp2/MR5: Construction Waste Management - packaging is designed to be reusable or recyclable. See below for details.

MR3: Sourcing of Raw Materials (recycled content) – this product contains recycled material. Recycled content is shown above for all standard options. (regional materials) – this product is manufactured in Pittsburgh, PA. Contact for extraction information.

Green Globes™

3.2.5 Exterior Light Pollution - full light output data is available on Product Data Sheets. Contact for details.

3.3.5.6 Exterior Luminaires and Controls - energy efficient LEDs are available. LEDs do not contain mercury. Contact for details.

3.5.4.1 Construction Waste - packaging is designed to be reusable or recyclable. See below for details.

3.5.6.3 Deconstruction and Disassembly - this product can be disassembled to separate recyclable components

Estidama Pearl Rating System: Design & Construction, Version 1.0

LBo-10: Light Pollution Reduction - full light output data is available on Product Data Sheets. Contact for details.

SM-R1: Hazardous Material Elimination – product contains no ACMs and no CCA-treated timber

SM-R2/SM-13: Construction Waste Management - packaging is designed to be reusable or recyclable. See below for details.

SM-4: Design for Disassembly - this product can be disassembled to separate recyclable components

SITES v2 Rating System

Materials C5.3: Design for adaptability and disassembly - this product can be disassembled to separate recyclable components

Materials C5.5: Use recycled content materials - this product contains recycled material. Recycled content is shown above for all standard options.

Materials C5.6: Use regional materials - this product is manufactured in Pittsburgh, PA. Contact for extraction information.

HHWB C6.8: Reduce light pollution - full light output data is available on Product Data Sheets. Contact for details.



Green Building Standards continued

SITES v2 Rating System (continued)

HHWB C6.8: Reduce light pollution - full light output data is available on Product Data Sheets. Contact for details.

Construction C7.5: Divert construction and demolition materials from disposal - packaging is designed to be reusable or recyclable. See below for details.

O+M C8.5: Reduce outdoor energy consumption -energy efficient LEDs are available. Full light output data is available on Product Data Sheets.

Product Materials

Todate Materials								
Material	Description	Mainte- nance (0-5)*	Inherent Value (0-5)**	Biodegrad- able	Corrosion/ Wear Resistant	Rapidly Renewable	Recyclable	Scratch Resistant
Acrylic	Thermoplastic, petroleum-based polymer often used as a substitute for glass because of its high impact strength and clarity.	4	0		х		x	
Stainless Steel	Steel that is alloyed with chromium and other metals to improve corrosion-resistance.	3	4		х		х	

^{*}Maintenance ratings are assigned as follows: 0 – High level of maintenance required to keep up product performance and aesthetics; 5 – Absolutely no maintenance required to keep up product's visual appearance and performance characteristics;

Processes

Process	Description		
Casting	The process of creating a solid object by pouring molten metal into a mold and allowing it to cool.		
Cutting	A variety of methods may be used to cut through various materials.		
Forming	g A mechanical process used to alter the shape of metal.		
Machining A form of subtractive or additive manufacturing often requiring specialty tooling to physically rem material to achieve a desired geometry. Metal Finishing Applied using grinding/sanding wheels. Finishing produces a grained or brushed finish on the sudepending on the material will increase corrosion resistance.			
		Plastics Manufacture	Plastic is the common term for a wide range of synthetic or semi-synthetic organic solid materials used in industrial applications. Plastics are typically polymers of high molecular weight, and may contain other substances to improve performance or reduce costs.
Powdercoating	A solvent-free finishing method in which electrically charged particles of pigmented resins are sprayed onto a product. Electrical grounding of the coated object causes the charged powder to adhere to the surface. When baked in a curing oven the deposited powder melts and fuses together to form a durable, cross-linked coating		
Steel Making	Steel and stainless steel are made in one of two types of furnace: a Basic Oxygen Furnace (BOF) or an Electric Arc Furnace (EAF). A BOF is used to make steel from iron ore or from scrap steel; an EAF is used primarily to reprocess scrap steel.		
Welding	A process that joins two similar metals by causing coalescence. Usually accomplished by melting the work pieces and adding a filler material to form a pool of molten metal that cools to become a strong joint.		

Packaging Materials

ackaging materials				
Material	Material Type Description		Disposal	
Cardboard Box Small or light products are packaged in cardboard boxes. Reused for shipping, then re		Small or light products are packaged in cardboard boxes. Reused for shipping, then recycled.	Reuse/Recycle	
Cardboard Spacers		Used to provide impact cushioning between a product and its package or between two products.	Reuse/Recycle	
Plastic	Shrink wrap	Shrink wrap is used to protect the finish on products and also to hold padding to products.	Recyclable	
Wood	Pallet	Used in shipping. Reused onsite until no longer serviceable, then recycled.	Reuse/Recycle	



^{**}Inherent value ratings are assigned based on the material's scrap value: 0 – No scrap value, or negative scrap value, and/or no scrap market; 5 – High scrap value, accompanied by robust scrap market

Transport

Method	Туре	Description	
Boat Overseas Some product components are shipped by cargo ship from overseas			
Ground	Truck/Rail	Some incoming shipments and almost all outgoing shipments to customers are sent via ground transportation. This can include truck and often rail transport depending on the final destination. We are an EPA SmartWay® Transport Partner.	

Maintenance & Use

Maintenance or Use	Description		
Clean with Water and Mild Cleaner	This product requires a damp cloth and a mild, nontoxic cleaner for maintenance.	Mild, water-based cleaner	
Electricity – LED	Product is available with LED lamping.	NA	

Disposal

no podul				
Method	Description			
Disassemble Product can be disassembled to separate recyclable components				
Recyclable Metal and acrylic components are recyclable. LEDs may be recyclable in some areas.				
Recycling - Scrap	Materials can be sold for scrap			

Forms+Surfaces is dedicated to environmental responsibility. We maintain an Environmental Management System and are continually working to improve our impact through efficiency, material selection, vendor education, employee involvement, and an unwavering commitment to being exemplary corporate citizens. If you would like additional information, please contact our Sustainability Team at green@forms-surfaces.com.

