# VIVITELA<sup>TM</sup> LOOM GLASS

			DESIGN GUIDE			
PROJECT NAME:		DATE:				
JOB LOCATION:		SPECIFIER:				
PLEASE USE ADOBE READER OR ADOBE ACROBAT TO FILL OUT AND SAVE FORM. USING OTHER PROGRAMS COULD RESULT IN UNSAVED DATA.						
	APPL	ICATIONS				
If you select a Forms+Surfaces System, ple	ease skip the Project Details, Lite Descriptions a	nd Glass Characteristics sections.				
Forms+Surfaces Systems		Other Applications*				
LEVELr Wall Cladding System	LEVELc-2000 Elevator Interiors	Loose Lite(s)				
LEVELr Column System	Glass Doors	Other:				
LEVELr Elevator Interiors	Stile & Rail Doors	*For Other Applications, please fill out all sections.				
LEVELe Wall Cladding System						
LEVELe Column System						
LEVELe Elevator Interiors						
	PROJEC	CT DETAILS				
Please choose one option from each categ	ory.					
Installation Type	Glass Thickness	Environment	Lighting Conditions			
Captured Top & Bottom Only	5/16" (7.7 mm)	Interior, Standard Humidity	Natural			
Fully Framed	7/16" (11.1 mm)	Interior, High Humidity	Backlit			
Mounted to a Solid Substrate	9/16" (13.7 mm)	Exterior, Exposed Setting	Spotlight			
Curtain Wall/IGU		Exterior, Covered Setting	Other (please provide details):			
Post Mounted with Holes						
Water Feature						
		SCRIPTION				
Description (include modernmoleum if and						
Description (include part number, if available)		Quantity	Size (width x height)			
	GLASS CHA	RACTERISTICS				
Please choose one option from each catego	ory.					
Safety Standards		Profile				
Annealed		Flat				
Tempered*		Curved (please attach drawing)				
Heat Strengthened**						

\*Tempering is required for load bearing holes and cutouts. Please note that 5/16" laminated glass can only be tempered to a max of 47" x 80". \*\*Heat strengthening is recommended for glass over 50 square feet.

## FORMS+SURFACES®

© 2023 Forms+Surfaces® | All dimensions are nominal. Specifications and pricing subject to change without notice. For the most current version of this document, please refer to our website at www.forms-surfaces.com.

# VIVITELA<sup>TM</sup> LOOM GLASS

DESIGN	GUIDE

PROCESSING REQUIREMENTS							
Please choose <b>all</b> options that apply and provide de	etail as needed.						
Edges							
Seamed Edges	Тор	Bottom	Left Side	Right Side			
Flat Machine Polished Edges	Тор	Bottom	Left Side	Right Side			
Cuts							
Notches*	Yes	No					
Internal Cutouts*	Yes	No					
Pattern Cuts*	Yes	No					
Holes*	Yes	No					
ANSI							
ANSI logo on glass**	Yes	No					
ANSI logo type	American	Canadian					
ANSI logo placement	Standard	Custom***					
*'If yes, please attach drawing. **ANSI logo is required for elevator interiors. ***'If ANSI logo placement is custom, please provide details.							
		GLASS DESIGN C	HARACTERISTICS				
Please choose <b>one</b> option from each category.							
Configuration							
View							
Reflect							
Interlayer   Black   White   Custom Pantone, Sherwin Williams or Benjamin Moore color(s):							
Finish   Standard   Pearlex+   Standard / Pearlex+*   *One side Standard / one side Pearlex+ (View control	nfiguration only).						

#### T 800.451.0410 | www.forms-surfaces.com

## FORMS+SURFACES®

© 2023 Forms+Surfaces® | All dimensions are nominal. Specifications and pricing subject to change without notice. For the most current version of this document, please refer to our website at www.forms-surfaces.com.

### STANDARD PATTERNS

Please choose one pattern option below (as shown, all are in the Reflect configuration in Black).



### Understitch



NOTES

Please send completed forms to sales@forms-surfaces.com or contact us at 800.451.0410 with any questions.

#### T 800.451.0410 | www.forms-surfaces.com

FORMS+SURFACES®

© 2023 Forms+Surfaces® | All dimensions are nominal. Specifications and pricing subject to change without notice. For the most current version of this document, please refer to our website at www.forms-surfaces.com.